

TABLE OF CONTENTS



Biography	5	Brake Force and Corner Weight	37
Acknowledgments	5	Perfect Balance	38
Dedication	6	Static Weight Distribution	39
Foreword	6	The Second Law of Motion	39
Introduction	7	Dynamic Weight Distribution	40
Chapter 1: Energy Conversion	9	The Benefits of Perfect Balance	41
The Conservation of Energy	9	Front Brake Bias	43
Where Energy Comes From	10	Rear Brake Bias	43
Friction	10	Measuring Brake Balance	44
Kinetic Energy	11	Changing Brake Balance	44
Potential Energy	13	Chapter 5: Pedals, Boosters	
Energy Transformation	14	and Master Cylinders	46
Energy and the Brake System	14	Brake Pedal Components	46
Calculating Brake System Temperature	15	OEM Brake Pedals	47
Importance of Brake Sizing	15	Racing Brake Pedals	48
Chapter 2: Tires Stop the Car	18	Brake Boosters	48
The First Law of Motion	18	Vacuum Boosters	48
Brake Forces	18	Hydraulic Boosters	50
Tire Slip	19	Master Cylinders	50
How Brake Forces are Generated	20	Master Cylinder Selection	52
The Mu-Slip Curve	22	Rear Brake Pressure Reduction	54
Choosing the Best Tires	24	Balance Bars	54
Calculating Maximum Deceleration	25	Proportioning Valves	55
Chapter 3: Brake System Design	27	Chapter 6: Brake Fluid	58
Driver Applied Force	27	Brake Fluid 101	58
Brake System Overview	28	FMVSS116	58
Brake Corner Gain	33	Dry Boiling Point	60
Summing Forces	34	Wet Boiling Point	61
Overall Brake System Gain	34	Water Adsorption	61
Calculating Deceleration	34	DOT Ratings	61
Calculating Stopping Distance	34	Brake Fluid Compatibility	64
Brake System Modifications	35	Brake Fluid Maintenance	64
Chapter 4: Brake Balance	37	Brake Bleeding	65
		Chapter 7: Brake Lines and Hoses	69

TABLE OF CONTENTS



Hydraulic Circuit Design	69		
Brake Lines	70		
Flare Fittings	70		
Brake Hoses	71		
Banjo Fittings	72		
Stainless Steel Brake Hoses	73		
Chapter 8: Brake Calipers	76	Chapter 11: Sports Car Brake Upgrade	118
Hydraulic Gain	76	The Vehicle	119
Caliper Components	76	The Objective	119
Taper Wear	79	Picking the Right Parts	119
Piston Count	81	Bolting Them On	121
Caliper Mounting	82	The Results	124
One-Piece (Monoblock) Calipers	84		
Two-Piece Calipers	84	Chapter 12: Racecar Brake Upgrade	126
Knockback	84	The Vehicle	127
		The Objective	127
Chapter 9: Brake Pads	88	Front Brake Upgrade	127
Brake Pad Terminology	88	Rear Brake Upgrade	129
Coefficient of Friction	90	Apply System Upgrade	131
Coefficient of Friction Stability	91	Hoses, Fluids, and Pads	132
Brake Pad Fade	91	The Results	132
Friction Material Categories	92		
Friction Material Chemistries	93	Chapter 13: Muscle Car Brake Upgrade	133
Friction Mechanisms	96	The Vehicle	133
Brake System Break-In	97	The Objective	134
		Drum Brakes 101	134
Chapter 10: Brake Rotors	100	Picking The Right Parts	134
A Rotor Refresher	100	Bolting Them On	135
Rotor Terminology	101	Buttoning it Up	138
Effective Radius	103	The Results	138
Rotor Sizing	103		
Static Weight and Rotational Inertia	103	Chapter 14: Hot Rod Brake Upgrade	139
Rotor Cooling	104	The Vehicle	139
One-Piece (Fixed) Rotors	107	The Objective	139
Two-Piece (Floating) Rotors	107	Front Brake Upgrade	139
Solid Rotors	109	Brake Pedal Considerations	140
Vented Rotors	110	Master Cylinder Upgrade	142
Cross-Drilled Rotors	111	Brake Line and Proportioning	
Slotted Rotors	112	Valve Installation	142
Rotor Inspection	113	Brake Hoses	143
Thickness Variation	115	Brake Fluid Selection	143
		Parking Brake Installation	144
		The Results	144



HOT ROD BRAKE UPGRADE

In many ways, hot rod builders are on their own when it comes to brake system component selection and system design. Unlike any of the production-based brake upgrades discussed this far, building a hot rod from scratch (or even from a kit) entails a unique collection of brake system considerations and constraints. With custom frames, powerful drivelines, modified bodies, and cut-and-paste suspension systems, there is little opportunity to learn from the original vehicle when the time comes to create your own hot rod brake system.

Yet the laws of physics still apply in these applications, making basic brake system design criteria just as important here as they were in Chapters 11, 12, and 13. The pages that follow will expose you to some of the most common design compromises, hardware considerations, and installation pitfalls that are either unique to, or exaggerated by, hot rod brake systems.

The Vehicle

The subject of this hot rod brake upgrade project began life as a 1940 Ford pickup truck. Although it still possesses some token bits of the original body and frame, little else resembles what rolled off of the assembly line over 60 years ago. Custom roadster coachwork, independent front suspension, Chevy power under the hood, and a host of complex chassis changes only begin to describe the level of change this truck has experienced.

Although originally equipped with hydraulic brakes (mechanical brakes were only dropped the year before in 1939), the single-circuit master cylinder and four-wheel drum brake layout was dated at



We were fortunate to catch this 1940 Ford hot rod pickup in the middle of its own brake upgrade project. When embarking on your own hot rod brake system upgrade, it sure helps to have the vehicle up off the ground in a clean and well-lit garage. If possible, having most of the body and powertrain out of the way makes the job that much easier. (Randall Shafer)

best. Therefore, as long as the rest of the truck was being significantly modified and updated, the brake system was upgraded as well.

The Objective

Like most vehicles of this type, this hot rod was primarily designed for cruising along on a Sunday afternoon drive. Therefore, increased thermal capacity was not high on the list of needs or wants. At the same time, optimizing brake pedal feel was not critical for the truck's intended use. In short, the most important

brake system performance requirement was to slow the truck in a stable fashion during emergency-type events. Naturally, the parts had to look good (since that's a big part of what hot rodding is all about), but performing a single stop quickly and reliably from a moderate speed was the most stringent brake system performance design target.

Front Brake Upgrade

The forward frame rails of the truck had already been modified to accept one of the most common independent front



It took a significant amount of modification to adapt a Mustang II front suspension to the stock front frame rails. However, the front brake hardware remains essentially unchanged from the Mustang II design. Note that many hot rodders upgrade their Mustang II front end with a set of 11.0-inch diameter rotors and aftermarket caliper mounting brackets. (Randall Shafer)

suspensions used in the hot rodding community. Lifted straight from a Ford Mustang II, this setup can be found hanging off the front end of countless hot rods today. In this application, the upper and lower control arms had already been replaced with custom tubular pieces, but the front uprights, bearings, and brake hardware were straight from the Ford parts bin.

Chosen more for availability and fitment than for thermal mass and effective radius, the front rotors measured a relatively small 9.0 inches in diameter and 0.9 inches in thickness. Although the straight vanes in the vented friction discs were not expected to be as efficient as curved vanes would have been, any front rotors would be more thermally robust than the stock front drums.

Like the front rotors, the front calipers were chosen more for convenience than for performance. These remanufactured single-piston calipers were based on the



The Mustang II front brake calipers contain relatively large brake pads held in place by floating caliper bodies. The single piston in each caliper was designed to be offset relative to the center of the rotor friction disc, resulting in a larger effective radius. In plain English, this means higher gain is possible in a smaller package. (Randall Shafer)

original Mustang II floating design. Their compact dimensions were the final consideration, as this would lead to flexibility in wheel selection later in the project.

Although a more modern Ford rear axle had been installed, in the interest of both time and money it was decided to leave the rear drum brakes in place. Of course they would receive a fresh coat of paint and fresh internal components, but with so little weight over the rear tires there was no reason to improve their performance. Even though it was still a pickup truck, its heavy hauling days were over.

Brake Pedal Considerations

In 1940, vacuum boosters were still several decades away from becoming mainstream brake system components. Therefore, because the truck was originally built without a vacuum booster (in other words, built with manual brakes), the brake pedal ratio was exceptionally high compared to conventional standards. Employing a pedal ratio of approximately 8.0:1, the stock brake pedal was required to swing through a relatively long arc as brake pressure was generated in the master cylinder.

Since the truck's master cylinder was originally mounted beneath the floor of the vehicle, retrofitting a vacuum booster,



While the stock single-circuit master cylinder was swapped for a tandem unit, its location under the vehicle was retained. The tight confines dictated that an opening be cut in the floorpan to allow access to the brake fluid reservoir. Check out the elegant routing of the custom-bent brake lines! (Randall Shafer)